(For Printing ink and kelated materials)

December 6, 2006 Date:

45211-3041

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

P.O. Box 7027

728 North Yale

Villa Park, IL 60181

**EMERGENCY PHONE:** 800-535-5053

MANUFACTURERS CODE: PRODUCT CLASS: TRADE NAME:

Oil Base Ink Graphic Etching Process Magenta 2347

SECTION II - HAZARDOUS INGREDIENTS

.0087 Hypothiolate

SECTION III - PHYSICAL DATA

Boiling Range: 200 degrees F Type of Odor:

Heavier than air Vapor Density:

Evaporation Rate: Slower than ether Percent Volatile Wt: N/A

Liquid Density:

Appearance: Magenta

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F

Lowest Flash Point:

LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

Ull Base Ink

Graphic Etching Process Magenta

2347

### SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water

Eye Contact - Flush eyes with water

### SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

### SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:

Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

# SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

## SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

## SECTION X - DISCLOSURE

## Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.