Safety Data Sheet: CHEM-AQUA 900

Supercedes Date 02/10/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name CHEM-AQUA 900 Recommended use Water treatment chemical Information on Manufacturer CHEM-AQUA, INC

BOX 152170

IRVING, TEXAS 75015

Product Code 0049 Chemical nature Aqueous solution **Emergency Telephone Number** CHEMTREC® 800-424-9300 Telephone inquiry 972-579-2477

Issuing Date 11/25/2014

2. HAZARD IDENTIFICATION

Physical State Liquid **Odor** Woody Color dark brown

GHS

Classification

Physical Hazards

Substances/mixtures corrosive to metal Category 1

Health Hazard

Skin Corrosion/Irritation Category 1 Serious Eye Damage/Eye Irritation Category 1 Respiratory Sensitization Category 1 Skin Sensitization Category 1

Other hazards None

Labeling

Signal Word **DANGER**



Hazard Statements

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H334 - May cause allergy or asthma symptoms or breathing difficulties if P272 - Contaminated work clothing should not be allowed out of the workplace inhaled

H290 - May be corrosive to metals

Precautionary Statements

P280 - Wear protective gloves, protective clothing, eye protection and face protection.

P264 - Wash face, hands and any exposed skin thoroughly after handling.

P260 - Do not breathe mist.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower

P333 + P313 - If skin irritation or rash occurs, get medical attention

P363 - Wash contaminated clothing before reuse

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a physician

P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P342 + P311 - If experiencing respiratory symptoms, call a physician

P301+ P330 + P331 - IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Call a

physician if unwell.

P406 - Store in a corrosion-resistant container.

P390 - Absorb spillage to prevent damage

P501 - Dispose of contents and container in accordance with applicable regulations.

5 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION / INFORMATION ON INGREDIENTS Component CAS-No Weight % 7757-83-7 Sodium sulfite 10-30

Sodium lignosulfonate 8061-51-6 3-7

**

4. FIRST AID MEASURES

General advice Do not get in eyes, on skin or on clothing. Do not breathe mist.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue

flushing for at least 15 minutes. Get medical attention immediately.

Skin Contact Remove immediately all contaminated clothing. Wash off immediately with plenty of water for at least

15 minutes. Get medical attention immediately.

Inhalation Move to fresh air. In case of shortness of breath, give oxygen. If breathing has stopped, apply artificial

respiration. Get medical attention immediately.

Ingestion Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention immediately. Never

give anything by mouth to an unconscious person.

Notes to physician The product causes burns of eyes, skin and mucous membranes. Control of circulatory system,

shock therapy if needed. May cause sensitization of susceptible persons.

5. FIRE-FIGHTING MEASURES

Flash Point Does not flash Method Not applicable Flammability Limits in Air % Hydrogen, by reaction with metals. Upper 75 Lower 4

Suitable Extinguishing Media

Water spray. Carbon dioxide (CO2). Foam. Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards arising from the chemical

Material can create slippery conditions. Contact with metals may evolve flammable hydrogen gas.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA Health 3 Flammability 1 Instability 0 HMIS Health 3 Flammability 1 Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Use personal protective equipment. Ensure adequate ventilation. Prevent further leakage or spillage

if safe to do so. Material can create slippery conditions.

Environmental Precautions Do not flush into surface water or sanitary sewer system.

Methods for Containment Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth,

diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national

regulations (see section 13).

Methods for Cleaning Up Pick up and transfer to properly labeled containers.

Neutralizing Agent Acetic acid, diluted.

7. HANDLING AND STORAGE

Handling Do not get in eyes, on skin or on clothing. Do not breathe mist.

Storage Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Metal containers must be lined. Freezing will affect the physical condition but will not damage the

material. Thaw and mix before using.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Sodium lignosulfonate	No data available	15 mg/m ³ (vendor data)	No data available

Engineering Measures Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should

be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment

Eye/Face Protection Tightly fitting safety goggles. Face-shield.

Skin Protection Wear suitable protective clothing, Impervious gloves.

Respiratory Protection In case of inadequate ventilation wear respiratory protection. When workers are facing

concentrations above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations Wear protective gloves/clothing. Ensure that eyewash stations and safety showers are close to the

workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liquid Viscosity Non viscous dark brown Color Odor Woody Opaque **Odor Threshold** Not applicable **Appearance** pН 12.4 Specific Gravity 1.18 **Evaporation Rate** 0.49 (Butyl acetate=1) Percent Volatile (Volume) 83.5 VOC Content (%) VOC Content (g/L) 0

Vapor Pressure 14.42 mmHg @ 70°F Vapor Density 0.6 (Air = 1.0)Solubility n-Octanol/Water Partition No data available Completely soluble Melting Point/Range No data available **Decomposition Temperature** No data available **Boiling Point/Range** 220 °F / 104 °C Flammability (solid, gas) No data available Flash Point Not applicable Does not flash Method

Autoignition Temperature No information available.

Flammability Limits in Air % Hydrogen, by reaction with metals. Upper 75 Lower 4

10. STABILITY AND REACTIVITY

Chemical Stability Stable. Hazardous polymerization does not occur.

Conditions to Avoid None known

Incompatible Products Strong oxidizing agents, Strong acids.

Hazardous Decomposition Products Carbon oxides, Sulfur oxides, Hydrogen sulfide, Sulfur compounds,

Hydrogen, by reaction with metals.

Possibility of Hazardous Reactions

None under normal processing

11. TOXICOLOGICAL INFORMATION

Product Information No information available.

The following values are calculated based on chapter 3.1 of the GHS document (Rev. 3, 2009):

Oral LD50 5,358.71

Dermal LD50 No information available
Inhalation LC50
Gas No information available

Mist 36.22

 Mist
 36.22

 Vapor
 36.22

Principle Route of Exposure Skin contact, Eye contact, Inhalation.

Primary Routes of Entry Skin Absorption, Inhalation.

Acute Effects

Eyes Corrosive to the eyes and may cause severe damage including blindness.

Skin Causes skin burns. May cause allergic skin reaction.

Inhalation Harmful by inhalation. Causes burns. May cause allergic respiratory reaction.

Ingestion If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the

esophagus and the stomach. May produce an allergic reaction.

Chronic Toxicity Inhaled corrosive substances can lead to a toxic edema of the lungs. May cause sensitization by

skin contact. May cause sensitization by inhalation.

Target Organ EffectsRespiratory system, Immune system, Central nervous system.Aggravated Medical ConditionsSkin disorders, Respiratory disorders, Neurological disorders.

Component Information

Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
Sodium sulfite	= 820 mg/kg (Rat)	no data available	> 22 mg/L (Rat) 1 h	no data available	no data available

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Sodium sulfite	no data available	Skin sensitization,	no data available	no data available	Respiratory system,
		respiratory sensitization			Immune system, CNS

Carcinogenicity

Component	ACGIH	IARC	NTP	OSHA	Other
Sodium sulfite	not applicable	Group 3	not applicable	not applicable	not applicable

12. ECOLOGICAL INFORMATION

Product Information
Component Information

No information available.

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
Sodium sulfite	no data available	no data available	EC50 = 770 mg/L 17 h	no data available	-4

Persistence and Degradability
Bioaccumulation
No information available.
No information available.
No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal Dispose of in accordance with local regulations.

Container Disposal Empty containers should be taken for local recycling, recovery, or waste disposal

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name Corrosive liquid, basic, organic, n.o.s.

 Hazard Class
 8

 UN-No
 UN3267

 Packing Group
 II

Description UN3267, Corrosive liquid, basic, organic, n.o.s.,(Sodium lignosulfonate), 8, PG II

TDG

Hazard Class 8
UN-No UN3267
Packing Group II

ICAO

UN-No UN3267

Proper Shipping Name Corrosive liquid, basic, organic, n.o.s.

Hazard Class 8
Packing Group ||

Shipping Description UN3267, Corrosive liquid, basic, organic, n.o.s., (Sodium lignosulfonate), 8, PG II

IATA

UN-No UN3267

Proper Shipping Name Corrosive liquid, basic, organic, n.o.s.

Hazard Class 8
Packing Group ||

Shipping Description UN3267, Corrosive liquid, basic, organic, n.o.s.,(Sodium lignosulfonate), 8, PG II

IMDG/IMO

Proper Shipping Name Corrosive liquid, basic, organic, n.o.s.

Hazard Class 8
UN-No UN3267
Packing Group II

Shipping Description UN3267, Corrosive liquid, basic, organic, n.o.s.,(Sodium lignosulfonate), 8, PG II

15. REGULATORY INFORMATION

Inventories

TSCA Complies
DSL Complies

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazardous Categorization

SARA 311/312 Hazardous Categorization							
Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of	Reactive Hazard			
			Pressure Hazard				
Yes	Yes	No	No	No			

CERCLA

16. OTHER INFORMATION

Prepared By Adrienne McKee

 Supercedes Date
 02/10/2014

 Issuing Date
 11/25/2014

Reason for Revision
Glossary
No information available.
No information available.
No information available.

CHEM-AQUA, INCassumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.