

**Material Name: ULTRABOND ECO 710** ID: SAH00435

# Section 1 - Chemical Product and Company Identification

Material Name: ULTRABOND ECO 710

**Product Use** 

Flooring Adhesive **Manufacturer Information** USA and Puerto Rico

MAPEI

1144 East Newport Center Drive Deerfield Beach, FL 33442

Phone: 1-954-246-8888

Canada MAPEI

2900 Francis-Hughes Avenue

Laval, QC H7L 3J5 Phone: 1-450-662-1212

IN THE EVENT OF A CHEMICAL EMERGENCY INVOLVING A SPILL, LEAK, FIRE, EXPLOSION, EXPOSURE OR ACCIDENT, CONTACT THE FOLLOWING NUMBERS:

Emergency 24 hour numbers:

(USA) CHEMTREC 1-800-424-9300 (Canada) CANUTEC 1-631-996-6666

# **Section 2 - Hazards Identification**

### **Emergency Overview**

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This product is irritating to the eyes.

#### **Hazard Statements**

CAUTION! IRRITANT. Irritating to eyes. Wear suitable gloves and eye/face protection. Keep out of the reach of

**Potential Health Effects: Eyes** 

This product is irritating to the eyes.

Potential Health Effects: Skin

This product may cause irritation to the skin.

**Potential Health Effects: Ingestion** 

Ingestion of this product may cause nausea, vomiting and diarrhea.

Potential Health Effects: Inhalation

This product may cause irritation to the respiratory system.

**Medical Conditions Aggravated by Exposure** 

Hypersensitivity to product, allergies, and skin or respiratory disorders

Potential Environmental Effects

None identified.

HMIS Ratings: Health: 1 Fire: 0 Reactivity: 0 Pers. Prot.: Safety glasses, gloves

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

# Section 3 - Composition / Information on Ingredients

| CAS#        | Component  | Percent |
|-------------|--|---------|
| 64742-52-5  | Naphthenic oil   | 10-30   |
| 1332-58-7   | Kaolin   | 10-30   |
| 57-13-6     | Urea   | 1-5     |
| 8050-26-8   | Resin acids and Rosin acids, esters with pentaerythritol | 1-5     |
| Proprietary | Modified rosin   | 1-5     |

Page 1 of 6 Issue Date: 20 August 2009 Revision: 1.0000 Print Date: 8/20/2009

Material Name: ULTRABOND ECO 710 ID: SAH00435

# \* \* \* Section 4 - First Aid Measures \* \* \*

#### First Aid: Eyes

In case of contact, immediately flush eyes with large amounts of water, continuing to flush for 15 minutes. If irritation persists get medical attention.

First Aid: Skin

For skin contact, flush with large amounts of water. If irritation persists, get medical attention.

#### First Aid: Ingestion

For ingestion, flush out mouth with water. If ingestion of a large amount does occur, seek medical attention. Do not induce vomiting.

#### First Aid: Inhalation

If inhaled, immediately remove the affected person to fresh air. If the affected person is not breathing, apply artificial respiration. If symptoms persist, get medical attention.

### First Aid: Notes to Physician

Provide general supportive measures and treat symptomatically.

# \* \* \* Section 5 - Fire Fighting Measures \* \* \*

#### **General Fire Hazards**

See Section 9 for Flammability Properties.

This product is an aqueous mixture which will not burn. If evaporated to dryness, the solid residue may pose a moderate fire hazard.

#### **Hazardous Combustion Products**

Irritating and toxic gases or fumes may be released during a fire. Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

# **Extinguishing Media**

Dry chemical (preferred), foam, water.

# Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

### NFPA Ratings: Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

# \* \* \* Section 6 - Accidental Release Measures \* \* \*

# **Personal Precautions**

Wear appropriate protective equipment and clothing during clean-up.

#### **Containment Procedures**

Dike the spilled material, where this is possible. Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps. Scoop up used absorbent into drums or other appropriate container.

### **Environmental Precautions**

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

#### Clean-Up Procedures

Attempt to reclaim the free product, if this is possible. Shovel the material into waste container. Thoroughly wash the area with water after a spill or leak clean-up. Keep out of the reach of children.

#### **Evacuation Procedures**

None identified.

# **Special Procedures**

Regulations vary. Consult local authorities before disposal.

# \* \* \* Section 7 - Handling and Storage \* \* \*

# **Handling Procedures**

Avoid getting this material into contact with your skin and eyes. Avoid breathing vapors or mists of this product. Wash hands after handling and before eating. Keep out of the reach of children.

Material Name: ULTRABOND ECO 710 ID: SAH00435

### **Storage Procedures**

Store in a cool, dry, well-ventilated area. Store at ambient temperature and atmospheric pressure. Keep out of

# \* \* \* Section 8 - Exposure Controls / Personal Protection \* \* \*

# **A: Component Exposure Limits**

# Kaolin (1332-58-7)

| Naumi (1332-      | 50-1)  |
|-------------------|--|
| ACGIH:            | 2 mg/m3 TWA respirable fraction, particulate matter containing no asbestos and <1% crystalline silica  |
| OSHA (Final):     | 15 mg/m3 TWA total dust; 5 mg/m3 TWA respirable fraction   |
| NIOSH:            | 10 mg/m3 TWA total dust; 5 mg/m3 TWA respirable dust   |
| Alberta:          | 2 mg/m3 TWA (respirable)   |
| British Columbia: | 2 mg/m3 TWA particulate particulate matter containing no asbestos and less than 1% crystalline silica  |
| Manitoba:         | 2 mg/m3 TWA respirable fraction particulate matter containing no asbestos and <1% crystalline silica   |
| New Brunswick:    | 2 mg/m3 TWA particulate matter containing no asbestos and < 1% crystalline silica, respirable fraction |
| NW Territories:   | 5 mg/m3 TWA respirable mass; 10 mg/m3 TWA total mass   |
| Nova Scotia:      | 2 mg/m3 TWA respirable fraction, particulate matter containing no asbestos and <1% crystalline silica  |
| Nunavut:          | 5 mg/m3 TWA respirable mass; 10 mg/m3 TWA total mass   |
| Ontario:          | 2 mg/m3 TWAEV respirable containing no asbestos and less than 1% crystalline silica                    |
| Quebec:           | 5 mg/m3 TWAEV respirable dust, containing no asbestos and less than 1% crystalline silica              |
| Saskatchewan:     | 2 mg/m3 TWA (respirable fraction)  |
|                   | 4 mg/m3 STEL (respirable fraction)   |
| Yukon:            | 30 mppcf TWA; 10 mg/m3 TWA   |
|                   | 20 mg/m3 STEL  |

### **Engineering Controls**

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits. Local exhaust is suggested for use, where possible, in enclosed or confined spaces.

#### PERSONAL PROTECTIVE EQUIPMENT

# Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields.

# Personal Protective Equipment: Skin

The use of nitrile-latex gloves is recommended.

# **Personal Protective Equipment: Respiratory**

Not normally needed. If airborne concentrations are above the applicable exposure limits, use NIOSH approved

respiratory protection.

#### Personal Protective Equipment: General

Launder contaminated clothing before reuse. Use good industrial hygiene practices in handling this material.

# \* \* \* Section 9 - Physical & Chemical Properties \* \* \*

| Appearance:                     | Beige paste     | Odor:                           | Slight latex odor |
|---------------------------------|-----------------|---------------------------------|-------------------|
| Physical State:                 | Paste           | pH:                             | 8.0 - 10.0        |
| Vapor Pressure:                 | N/A             | Vapor Density:                  | N/A               |
| Boiling Point:                  | 212° F (100° C) | Melting Point:                  | N/A               |
| Solubility (H2O):               | Dispersible     | Specific Gravity:               | 1.30 - 1.60       |
| Evaporation Rate:               | Same as water   | VOC:                            | 6 g/L             |
| Octanol/H2O Coeff.:             | N/A             | Flash Point:                    | N/A               |
| Flash Point Method:             | N/A             | Upper Flammability Limit (UFL): | N/A               |
| Lower Flammability Limit (LFL): | N/A             | Burning Rate:                   | N/A               |
| Auto Ignition:                  | N/A             |                                 | _                 |

# **Physical Properties: Additional Information**

The data provided in this section is to be used for product safety handling purposes. Please refer to Product Data Sheets, Certificates of Conformity or Certificates of Analysis for chemical and physical data for determinations of quality and for formulation purposes.

Material Name: ULTRABOND ECO 710 ID: SAH00435

# \* \* \* Section 10 - Chemical Stability & Reactivity Information \* \* \*

#### **Chemical Stability**

Stable under normal conditions.

#### **Chemical Stability: Conditions to Avoid**

Do not freeze.

# Incompatibility

This product may react with strong acids, bases and oxidizing agents.

# **Hazardous Decomposition**

Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition. Upon decomposition, this product may emit fumes of carbon monoxide, carbon dioxide, oxides of nitrogen, and other organic compounds.

# **Possibility of Hazardous Reactions**

Will not occur.

# \* \* \* Section 11 - Toxicological Information \* \* \*

#### **Acute Dose Effects**

#### A: General Product Information

No information available for the product.

## B: Component Analysis - LD50/LC50

### Naphthenic oil (64742-52-5)

Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >5000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg Urea (57-13-6)

Oral LD50 Rat 8471 mg/kg

### Carcinogenicity

# A: General Product Information

No information available for the product.

#### **B: Component Carcinogenicity**

Kaolin (1332-58-7)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

## Sensitization

No information available for the product.

# \* \* \* Section 12 - Ecological Information \* \* \*

#### **Ecotoxicity**

#### **A: General Product Information**

No information available for the product.

# **B: Component Analysis - Ecotoxicity - Aquatic Toxicity**

Naphthenic oil (64742-52-5)

| Test & Species                 |            | Conditions |
|--------------------------------|------------|------------|
| 96 Hr LC50 Oncorhynchus mykiss | >5000 mg/L |            |
| 48 Hr EC50 Daphnia magna       | >1000 mg/L |            |

#### Urea (57-13-6)

| 5154 (51.15.5)                  |                  |            |  |  |  |  |
|---------------------------------|------------------|------------|--|--|--|--|
| Test & Species                  |                  | Conditions |  |  |  |  |
| 96 Hr LC50 Poecilia reticulata  | 16200-18300 mg/L |            |  |  |  |  |
| 24 Hr EC50 Daphnia magna Straus | >10000 mg/L      |            |  |  |  |  |
| 48 Hr EC50 Daphnia magna        | 3910 mg/L        | [Static]   |  |  |  |  |

Material Name: ULTRABOND ECO 710 ID: SAH00435

# \* \* \* Section 13 - Disposal Considerations \* \* \*

#### **US EPA Waste Number & Descriptions**

#### A: General Product Information

No additional information available.

#### **B: Component Waste Numbers**

No EPA Waste Numbers are applicable for this product's components.

#### **Disposal Instructions**

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

# \* \* \* Section 14 - Transportation Information \* \* \*

# **International Transportation Regulations**

Not regulated as dangerous goods.

# \* \* \* Section 15 - Regulatory Information \* \* \*

# **US Federal Regulations**

### **A: General Product Information**

All components are on the U.S. EPA TSCA Inventory List. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

### **B: Component Analysis**

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

## **State Regulations**

#### **A: General Product Information**

Other state regulations may apply. Check individual state requirements.

# **B: Component Analysis - State**

The following components appear on one or more of the following state hazardous substances lists:

| Component | CAS       | CA | MA  | MN  | NJ  | PA  | RI  |
|-----------|-----------|----|-----|-----|-----|-----|-----|
| Kaolin    | 1332-58-7 | No | Yes | Yes | Yes | Yes | Yes |
| Urea      | 57-13-6   | No | No  | Yes | No  | No  | No  |

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains a chemical known to the state of California to cause cancer.

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects.

# **Canadian WHMIS Information**

## **A: General Product Information**

Not regulated

# **B: Component Analysis - WHMIS IDL**

No components are listed in the WHMIS IDL.

# **Additional Regulatory Information**

#### **A: General Product Information**

Supplier(s) of proprietary component(s) state that these components are contained on the TSCA inventory.

**B: Component Analysis - Inventory** 

| Component  | CAS#       | TSCA | CAN | EEC    |
|--|------------|------|-----|--------|
| Naphthenic oil   | 64742-52-5 | Yes  | DSL | EINECS |
| Kaolin   | 1332-58-7  | Yes  | DSL | EINECS |
| Urea   | 57-13-6    | Yes  | DSL | EINECS |
| Resin acids and Rosin acids, esters with pentaerythritol | 8050-26-8  | Yes  | DSL | EINECS |

# \* \* \* Section 16 - Other Information \* \* \*

Reference

15-2114-53

Page 5 of 6 Issue Date: 20 August 2009 Revision: 1.0000 Print Date: 8/20/2009

Material Name: ULTRABOND ECO 710 ID: SAH00435

#### Other Information

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

#### Key/Legend

NA = Not available or Not Applicable. ACGIH = American Conference of Governmental Industrial Hygienists. NFPA = National Fire Protection Association. EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration., NJTSR = New Jersey Trade Secret Registry.

Contact: Product Safety Specialist Contact Phone: 1-954-246-8888

End of Sheet SAH00435