### MATERIAL SAFETY DATA SHEET

(For Printing Ink and Related Materials)

July 31, 2014 Date:

SECTION I

MANUFACTURED BY: Graphic Chemical & Ink Company

> P.O. Box 7027 728 North Yale

Villa Park, IL 60181

EMERGENCY PHONE: 800-535-5053

PRODUCT CLASS: TRADE NAME: **MANUFACTURERS** 

CODE:

Oil Base Ink Permanent Process Red 1929

SECTION II - HAZARDOUS INGREDIENTS

SECTION III - PHYSICAL DATA

Boiling Range: 200 degrees F Type of Odor:

200 degrees F Type of Odor:
Heavier than air Evaporation Rate: Slower than ether Vapor Density:

Liquid Density: Percent Volatile Wt: N/A

Appearance: Red

SECTION IV - FIRE & EXPLOSION DATA

Flash Point Category: 550 Degrees F

Lowest Flash Point:

LEL:

Extinguishing Media: Foam, CO2, Dry Chemical or Water Fog

Special Fire Fighting Procedure: Water may be used to cool container

Unusual Fire & Explosion Hazards: None

PRODUCT CLASS:

ASS: TRADE NAME:

MANUFACTURERS

CODE:

Oil Base Ink Permanent Process Red

1929

## SECTION V - HEALTH HAZARD DATA

Threshold Limit Value: Not established

Effects of Overexposure: None known

Emergency First Aid: Skin Contact - Wash affected area with soap & water

Eye Contact - Flush eyes with water

## SECTION VI - REACTIVITY DATA

Product Stability: Stable

Conditions to Avoid:

## SECTION VII - SPILL OR LEAK PROCEDURES

Procedure when material is spilled or released:

Ordinary clean up procedure. Sweep or wipe up. Dispose as any grease or oily material.

Waste disposal method:

# SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Adequate to prevent accumulation of vapors.

Protective Equipment (Respiratory, Eye, Etc.): None necessary

### SECTION IX - SPECIAL PRECAUTIONS

Storage & Handling:

#### SECTION X - DISCLOSURE

Disclosure Information:

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein.