

DATE:

MATERIAL SAFETY DATA SHEET

FOR PRINTING INK AND RELATED MATERIALS

NAPIM 11-7
(Rev. 6-76)

Section I

MANUFACTURER'S NAME HANDSCHY INDUSTRIES, INC.		EMERGENCY PHONE NO. (312) 276-6400
STREET ADDRESS (No., City, State, Zip) 2525 ELSTON AVE., CHICAGO, IL 60647		
PRODUCT CLASS COMPOUND	TRADE NAME SETSWELL	
MANUFACTURERS CODES MS-679		

Section II — HAZARDOUS INGREDIENTS

Section III — PHYSICAL DATA

BOILING RANGE F° 700	APPEARANCE STRAW COLORED PASTE	TYPE OF ODOR LINSEED
VAPOR DENSITY: HEAVIER <input type="checkbox"/> LIGHTER <input type="checkbox"/> vs. air N.A.	EVAPORATION RATE vs. Butyl Acetate	FASTER
LIQUID DENSITY: HEAVIER <input type="checkbox"/> LIGHTER <input checked="" type="checkbox"/> vs. water		SLOWER X
	PERCENT VOLATILE WT.	0

Section IV — FIRE & EXPLOSION DATA

FLASH POINT CATEGORY (OSHA)	III B	LOWEST FLASH POINT	345°F	LOWER EXPLOSIVE LIMIT	
-----------------------------------	-------	-----------------------	-------	-----------------------------	--

EXTINGUISHING MEDIA

SPECIAL FIRE FIGHTING PROCEDURE:

WATER OR FOAM MAY CAUSE FROTHING, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT BURNING LIQUID.

UNUSUAL FIRE & EXPLOSION HAZARDS

WATER OR FOAM MAY CAUSE FROTHING, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT BURNING LIQUID.

THIS FORM HAS BEEN SUBMITTED TO U.S.D.O.L. AS ESSENTIALLY SIMILAR TO OSHA FORM 20 AND IS SUPPLIED AS AN INDUSTRY SERVICE BY THE NATIONAL ASSOCIATION OF PRINTING INK MANUFACTURERS INC. (Information on this form is supplied by the individual ink manufacturer)

Section V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE

SKIN CONTACT: PROLONGED CONTACT MAY CAUSE IRRITATION.

EYE CONTACT : MAY CAUSE IRRITATION & REDNESS.

INGESTION : MAY CAUSE ABDOMINAL IRRITATION, NAUSEA AND VOMITING.

PRIMARY ROUTE(S) OF ENTRY:

DERMAL

INHALATION

EMERGENCY AND FIRST AID PROCEDURES

SKIN CONTACT: WASH WITH PLENTY OF WATER AND SOAP. REMOVE CONTAMINATED CLOTHING & LAUNDRER BEFORE REUSE. NECESSARY

EYE CONTACT : FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION IF*

INGESTION: INDUCE VOMITING AND GET MEDICAL ATTENTION IMMEDIATELY.

Section VI - REACTIVITY DATA

PRODUCT STABILITY

STABLE

UNSTABLE

CONDITIONS TO AVOID NONE

Section VII - SPILL OR LEAK PROCEDURES

PROCEDURE WHEN MATERIAL SPILLED OR RELEASED

MOP UP WITH WET MOP, AND DISCARD.

WASTE DISPOSAL METHOD DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, & LOCAL REGULATIONS.

Section VIII - SPECIAL PROTECTION INFORMATION

VENTILATION GENERAL EXHAUST.

PROTECTIVE GLOVES RECOMMENDED.

RESPIRATORY PROTECTION NONE REQUIRED IN NORMAL HANDLING

EYE PROTECTION OSHA STANDARD CHEMICAL SPLASH GOGGLES ARE ADVISED.

OTHER PROTECTIVE EQUIPMENT

Section IX - SPECIAL PRECAUTIONS

HANDLING AND STORING

STORE AT 35°F - 120°F IN GLASS OR PLASTIC CONTAINERS. KEEP CONTAINER CLOSED AND LABELED.

OTHER PRECAUTIONS AVOID CONTACT WITH SKIN & EYES. WASH WITH SOAP & WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES.